

Call: **(802) 891-9191**

**2023 TYM T224 W/ MOWER**

**\$16,500**



422 ROUTE 7 SOUTH  
MILTON VT, 05468

[Scan QR Code or Click Here](#)



VIN: N/A

STK#: 44

EXTERIOR COLOR: RED

DRIVETRAIN: 4WD

CONDITION: NEW

COLOR: RED

MILEAGE: N/A

INTERIOR COLOR: BLACK

TRANSMISSION: AUTOMATIC

**DESCRIPTION/OPTIONS:** Engine manufacturer Yanmar 3TNV74F Type Natural Aspiration Gross engine power 21.5 hp | 16 kW PTO power 15.1 hp | 11.3 kW Rated engine speed 3200 rpm No. of cylinders 3 Displacement 60.6 cu. in. Air cleaner Single Dry Alternator 12V, 40A Fuel system IDI POWERTRAIN Transmission type HST No. of speeds 2-Range Max. traveling speed 8.4 mph Brakes Wet Disc Steering Hydrostatic Clutch N/A HYDRAULIC SYSTEM Pump type Single Gear Pump Implement flow 4.17 gpm Steering flow 2.11 gpm Total flow 6.28 gpm Category, 3-point hitch I (N) Hitch lift capacity 1100 lb Hitch lift capacity at 24 inches behind link ends 679 lb Lift control type Position No. of standard remote valves Optional (1) PTO PTO type Independent PTO control Electric/Hydro PTO rear 540 rpm CAPACITIES Fuel tank 6.6 gal Coolant 3.7 qt Crankcase 1.9 qt Transmission/Hydraulics system 3.6 gal Front axle 2.6 qt DIMENSIONS & WEIGHTS Overall length with 3-point hitch 94.2 in. Overall width 44.5 in. Wheelbase 53.1 in. Height to top of ROPS 86.6 in. Min. ground clearance 8.3 in. Min. turn radius without brakes 86.6 in. Weight with ROPS 1472 lb STANDARD TIRES R3 Turf - Front Turf Master 16x7.50-8 NHS TL 4PR R3 Turf - Rear Turf Master 24x12.00-12 NHS TL 4PR R4 Industrial - Front WT300 18x8.5-10 NHS TL 4PR R4 Industrial - Rear WT300 26x12.00-12 NHS TL 4PR Lift height 71.3 in. (1810 mm) Max. lift height under level bucket 64.8 in. (1646 mm) Clearance with bucket dumped 53.9 in. (1369 mm) Reach at maximum lift height 26.8 in. (680 mm) Max. dump angle 37° Reach with bucket on ground 49.5 in. (1258 mm) Max. rollback angle 23° Digging depth 4.1 in. (105 mm) Lift capacity 617 lb (280 kgf) Breakout force at ground level, pivot points 1235 lb (560 kgf) Bucket rollback force at ground line 1036 lb (470 kgf) Bucket capacity 5.7 cu. ft (0.16 cu. m) Self leveling NA Relief valve setting (Loader control valve) 1849 psi (130 kg/sq. cm)

Jackson Enterprises LLC



© 2022 AutoDrivenMarketing.com